

SALES • SERVICE • PARTS

POWER TEAM

www.acehydraulic.com

# DEMY TOOL • S & PNEUMATICS/A



Distributors of INDUSTRIAL TOOLS & SUPPLIES

some quantities limited

6720 VIP Parkway · Syracuse, New York 13211

Phone 315-454-8989 24 Hour Fax 315-455-9522

We Carry a Large Selection of Chisels for CHIPPING HAMMERS and JACK HAMMERS

LINCOLN Model 877

# **Metered Control Handle**

Pneumatic Model 8080

Welder / Cutting Torch,

**Cutting Attachment** 

Oxygen Regulator

Sparklighter

Tip Cleaners

for Oil and ATF

Medium Pressure Mechanical Dial Metering Control Valve

**SALE** \$389

Oxy-acetylene

Nozzle Tips (VM-W 0, 2, 4 • VM-C 0-3-101)

Astro Pneur

Torch Handle

Acetylene Regulator

Check Valve

Twin Hose

Goggles





Model 7685 1 1" Air Impact Wrench w/6" Extended Anvil 1,912 ft-lbs. of torque in both forward and reverse directions. All-aluminum casing and rocking dog

hammer. 6" extended anvil. 3 forward / 3 reverse speeds and an aluminum D-handle for more precise control. Exhaust port directs air away 395 from operator SAL

Model 31510

1/2 HP 6" Bench Grinder 120V, 2.8 Amp, 3/4" Wheel Width

Model 31520 3/4 HP 8" Bench Grinder 120V, 4.8 Amp, 1" Wheel Width

WITCH

# **Bench Utility Vises**

Model 648UHD Utilty HD Bench Vise 8" Jaw Width, 8-1/2" Jaw Opening LxWxH 22 x 11.8 x 11.4 inches Wt. 82.7 lbs.

Sale \$395

Model 656UHD Utility HD Bench Vise 6-1/2" Jaw Width, 6-1/4" Jaw Opening LxWxH 18.1 x 11 x 10.2 inches Wt. 52.1 lbs

Sale \$280

Model 676U Utility Bench Vise 6-1/2" Jaw Width, 6" Jaw Opening LxWxH 18.1 x 9.4 x 10.2 inches Wt. 39.7 lbs.

Sale \$210

Model 675U Utility Workshop Vise 5-1/2-Inch Jaw Width by 5-Inch Opening LxWxH 12 x 6 x 9 inches Wt. 27.97 lbs.

Sale \$154

Model 746 Mechanics Vise 6" Jaw, LxWxH 4.25 x 6 x 5 inches Wt. 64 lbs.

Sale \$395

Astro

# Pneumatic Air Riveters

Model PR36 Includes: 3/16-inch (4.8mm), 5/32inch (4mm), 1/8-inch (3.2mm),

3/32-inch (2.4mm)

Model PR14 Includes: 1/4-inch(6.4mm), 3/16-inch(4.8mm), 5/32-inch(4mm), 1/8inch(3.2mm), 3/32-inch(2.4mm)

SALE \$





Alemite Diaphragm Pumps are designed for both high volume transfer and dispensing a variety of low viscosity fluids including new oil, used oil, windshield washer fluid, antifreeze, and other materials. Air Inlet: 1/4'


Body: Aluminum Diaphragm: Buna Pressure: 100 PSI Inlet/Outlet: 1/2"



Model 8323 Air Operated Diaphragm Pump

Air Inlet Description Body Material Diaphragm Material Pressure Material Inlet/Outlet Delivery (GPM)
Recommended Fluids

1/2" 1" Diaphragm Pump Aluminum Buna 125 PSI



The Fast, Easy, economical way to clean up spills. Perfect for automotive, industrial, marine, collision and farm applications, Just connect to shop air, vacuum up the spill, empty into a waste cotainer. Patented process can vacuum up all kinds of fluids from anti-freeze to heavy weight hydraulic oils. Not to be used for gasoline

- \* Length: 48" Depth: 10.75"
- \* Fluid Capacity: 1.5 Gallons
- \* Nozzle Width: 10" \* Tank Diameter: 7'
- Bucket Wheels: 2" Casters

\* Weight: 8.2 lbs. \$69

Ingersoll Model Rand Super Duty Air Hammer

3000 blows per minute. Tough, one-piece alloy barrel provides long life; produces up to 3,000 blows per minute

Easy-to-maintain; includes "easy out" throttle valve assembly 1-year limited

manufacturer's warranty



Ingersoll Model 261 Rand

3/4" Super Duty Air Impact Wrench

Jumbo hammer mechanism. Up to 1,000ft.-lbs. of torque. Trouble-free, longer performance aided by Pressure-Feed Lube System. Compact and only 7 5/8" long Handle exhaust.

**SALE** 





3/4-In. Super Duty SALE Air Impact Wrench

1200 Ft. Lbs. of Torque Power to loosen the toughest fastener. Weighs less than 12 lbs. 6 vane motor for speed

- power with any 1/2-Inch hose air supply. Twin Hammer high performance clutch. Ergonomic handle exhaust keeps exhaust air away from the operator



This tool is lightweight, fast and very hard hitting. It is most often used on jobs where weight restrictions are in place such as ramps, bridge decks and some highway jobs. Equipped with a muffler.



- · Great for rust removal on chassis
- Great cleaning up steel wheel drums
- Ideal for surface clean-up work General purpose needle scaler • Rubber sleeve on handle for better comfort • Delivered with 2 sets of needles: • 19 x 1/8" (3 mm) for standard usage
- 29 x 5/64 " (2 mm) for finer usage

WE CARRY REPLACEMENT NEEDLES







cutting lock and durability

Recessed and concealed lock protectors for maximum security against drilling and

Enhanced lid bolster for added support

Finger-groove lid handle for easy Steel support arm to hold lid in

open position

**AMERICAN** Model Std. Cap. POWER PL 605-10 3/4 Ton Chain Product Thick Steel Construction Heat Treated Drop Forged Safety Hooks

Warranty

615-10 1.5 Ton 276.00 635-10 3 Ton 399.00 660-10 6 Ton 662.00 **Chain Hoist**  Different Chain Lengths Available On Request

410 212.00 1 Ton 5-YEAR Manufacturer's 405 1/2 Ton 179.00





#### Airmaster® Fan Company

Model 60007

# Portable Mancooler Fan

115V Belt Drive 42 In 115 Volt, 1 Phase, 2 Speed, ODP, 1/2 HP Motor 42" Diameter three bladed aluminum propeller Two speed rocker switch 8" steel wheels with rubber tires Handle with cord wrap 10 ft three conductor SJT tyupe cord **SALE** Guards black epoxy coated Barrel epoxy coated

#### Model Airmaster® Fan Company 78984 **Industrial 18" Low Stand Pivot** Fan/voke Mount Low stand pivot fan/yoke mount 1/8 Hp - Shipping weight 20 lbs Nickel chrome guards meet osha standards

115V, phase, 3 speed, totally enclosed, ball bearing motor Aluminum propellers 1.65 F.L. Amps - 1 Year warranty Four position easy reach switch Adjusts 360 degrees



**SALE** 

225.00

Motor: 115V, 1/3 HP, oscillating 1 Phase, 3-speed, totally enclosed air over ball bearing



# SUNEX® Model 7793B

1 year warranty - UL/CUL listed

#### 1/2 Ton Telescopic Transmission Jack

Foot activated pump pedal. Maximum height of 74 inches. Lowered telescopic rams enable the transmission to be transferred from the jack to the work table Nylon strap tie down secures the load to the saddle. Overload valve prevents jack from being used beyond its rated capacity

SALE \$

### norco

Model 72508

#### Fuel Tank Saddle Adapter

Handles automotive and light duty truck fuel tanks up to 40 gallon capacity. Tanks are to be emptied before handling. Four adjustable support risers with rubber pads protect the fuel tank and can be quickly positioned to fit many shapes and sizes. Includes two load restraint straps.

SALE **\$250** 



**Power Train Lift Table** 

Length 57.0 inches Load Capacity 1 pounds Max. Lifting Height 1.0 inches

SALE \$1959

#### EDELMANN Model 4431



'Standard' Series Filter/Regulator/ **Lubricator Combo** (1/2-14 NPT Inlet/Outlet)

5 - 125 psi range; 250 psi maximum inlet pressure at 175 F





**Model B65425** 10.000 PSI

Air Hydraulic Pump

High strength aluminum reservoir is lightweight and corrosion resistant. Suggest air pressure 90-175 PSI. Pressure relief valve for overload protection. Three position pedal provides cylinder advance, hold, or release positions.

Air exhaust muffler for quiet operation.

# **■ LETRIFY** Model L1380

#### Grease Gun Workforce Mega Power 12V Battery Powered

Inc: Charger and two 12 volt batteries Durable carrying case Delivers up to 8000 PSI No pumping required Holds 14 oz. grease cartridge

**SALE** \$139





Pump Ram Ram Ram Capacity 8.000 psi Ext Hgt Close Hgt 15-3/4 4 ton 11 B65115 10 ton 10,000 psi 19-3/4" 2.4 in<sup>2</sup>

Ram Model Capacity Eff Area GW B65114 1 0 in<sup>2</sup> 46 lbs



3/4 In. Drive 100-600 ft lbs

Ratchets in only one direction. Rubberized head. Selected reading is automatically locked in. Indicates desired torque by feel and sound. Accuracy +-4 percent right hand and +-6 percent left hand direction from 20-100 percent of capacity. Rugged non-slip metal handles.



• Two-way operation for either siphoning

or dispensing SALE • 1 gallon for every 12 revolutions • Heavy-duty 10" steel wheels

• Fill level gauge

SAMSON Model 303141 PM3 120Lb Keg Package 10 Ft Hose with Band Dolly



## **Model 3601** Pressurized Used Oil Receiver

For draining, transferring and evacuating motor oils, transmission and power steering fluids quickly. Offers excellent mobility, easy bowl positioning and simple-touse pressurized evacuation.

Tank Capacity 72.0 Qts./68.1 Lt **Drain Bowl Capacity** 11 Qts./10.4 Lt



# ACE HYDRAULIC & PNEUMATICS www.acehydraulic.com

TERMS and CONDITIONS: Prices subject to change without notice in accordance with manufacturing costs. We have the right to limit quantities. SUPPLIES MAY BE LIMITED. We are not responsible for typographical errors. All returns MUST be unused and in original box. NO RETURNS ON SPECIAL ORDERS. NO C.O.D.

88 lbs